



ZF LifeguardFluid 8

Automatic Transmission Fluid for ZF Automatic Passenger Car Transmissions (8HP)

Product description:

ZF LifeguardFluid 8 has been specially developed for usage in 8HP automatic passenger car transmissions from ZF. The friction behavior has been optimally adapted for this transmission and is consistent over the entire service life. These features are a prerequisite for perfect shifting characteristics and vibration-free operation. ZF LifeguardFluid 8 thus fulfills the most demanding requirements on the transmission's comfort behavior.

The additives, which are customized to the individual components, also provide specialized protection and thus increase the service life of all transmission components.

The optimized viscosity builds the foundation for maximized savings in fuel. The high-quality semi-synthetic base oil ensures that high thermal-oxidative stability is maintained throughout the transmission's entire service life. This product has a flat viscosity-temperature curve and is therefore perfectly suited for use in extremely cold or hot climates.

Application:

ZF LifeguardFluid 8 has been specially developed for usage in 8HP automatic transmissions and some 6HP automatic transmissions from ZF. The approvals for each specific case can be found in the ZF List of Lubricants TE-ML 11 (www.zf.com/schmierstoffe).

Please note that only ZF LifeguardFluid 8 or ZF LifeguardFluid 9 may be used for these transmissions (where applicable, also available as genuine spare part from the relevant Original Equipment Manufacturer). Using other oils can lead to various adverse effects, ranging from significant deterioration in shifting characteristics to transmission failure. In principle, an oil change is only necessary when repairs are carried out.

ZF automatic transmissions are generally filled with lifetime oil. However, due to the many factors influencing the service life of transmissions in individual operation, ZF recommends an oil change after 150,000 km for its transmissions.

In operating conditions with high temperatures and loads, or with unknown vehicle use in the past, it can make sense to change the transmission oil at shorter intervals.



ZF LifeguardFluid 8

Automatic Transmission Fluid for ZF Automatic Passenger Car Transmissions (8HP)

In these instances, only the approved transmission oil may be used for the oil change, and you must also ensure that the oil change is carried out according to the relevant ZF provisions.

Small container (up to 20 l) must be shaken vigorously for at least 15 s before removing the oil. Before removing oil, large container (more than 20 l) must be mixed with a suitable and clean stirrer (min. 1500 1 / min) for at least 60 min at room temperature.

Product properties:

Product no.		
S671.090.312	Bottle	1 l
S671.090.311	Canister	20 l
S671.090.310	Drum	209 l
S671.090.313	IBC	1,000 l
Characteristics (typical values)		
Color	Green	
Density at 15°C	846 kg/m ³	
Viscosity at 40°C	26 mm ² /s	
Viscosity at 100°C	5.6 mm ² /s	
Brookfield viscosity at -40°C	8,850 mPa.s	
Pour point	-42°C	
Flash point (COC)	206°C	