

Technical Data	Audi e-tron 55 quattro (265 kW)
Program for Germany	Status: 12/05/2018
Engine / electrics	
Peak electrical output in kW	265
Continuous electrical output in kW	100
Peak electrical output boost in kW	300
Electrical torque output in Nm (<i>lb-ft</i>)	561 (413.8)
Electrical torque output boost in Nm (<i>lb-ft</i>)	664 (489.7)
Battery type	Lithium-ion
Battery energy content in kWh	95
Start-stop / REM	no / yes
Max. electrical output at 12V in kilowatts	3
On-board voltage in volts	12
Emissions standard	-
Drivetrain / transmission	
Drive type	All-wheel drive
Transmission type	Two-stage planetary gearbox with single gear
Transmission ratio, front	9.205
Transmission ratio, rear	9.083
Reverse gear ratio / final drive ratio 1-2	Not available / 9.205
Suspension / steering / brakes	
Type and design of front-axle suspension	Five-link front axle; tubular anti-roll bar; air spring suspension
Type and design of rear-axle suspension	Five-link rear axle; tubular anti-roll bar; air spring suspension
Steering	Electromechanical progressive steering with speed-dependent power assistance
Steering ratio	15.9
Turning circle in m (<i>ft</i>)	12.2 (40.0)
Brake control system	Dual-circuit brake system with diagonal split, ESC/ABS/EBD, brake booster, hydraulic brake assist
Tires (basic)	255/55 R 19 111 H XL (Extra Load)
Wheels (basic)	Cast aluminum flow forming 8.5J x 19"
Performance / acoustics	
Top speed in km/h (<i>mph</i>)	200 (124.3)
Limited	yes
Electrical acceleration, 0-100 km/h (0-62.1 <i>mph</i>) in s	6.6
Electrical acceleration boost, 0-100 km/h (0-62.1 <i>mph</i>) in s	5.7
Exterior noise level when stationary / drive-past as per ECE R51.02 / drive-past as per ECE R51.03 in db (A)	- / - / 68
Consumption / range	
Combined electric power consumption in kWh/100 km (62.1 <i>mi</i>)*	26.2 - 22.5 (WLTP); 24.6 - 23.7 (NEFZ)
CO ₂ emissions combined in g/km (<i>g/mi</i>)	0
Electric range refers to the electric power consumption in the combined WLTP test cycle in km (<i>mi</i>)*	up to 417 (259.1)

Weights / loads	
Unladen weight without driver / with driver / gross weight limit in kg (<i>lb</i>)	2490 (5489.5) / 2565 (5654.9) / 3130 (6900.5)
Front / rear axle load limit in kg (<i>lb</i>)	1515 (3340.0) / 1740 (3836.0)
Trailer load limit on 8% / 12% gradient, braked // unbraked in kg (<i>lb</i>)	1800 (3968.3) / 1800 (3968.3) // 750 (1653.5)
Roof load limit / permissible nose weight in kg (<i>lb</i>)	75 (165.3) / 80 (176.4)
Capacities	
Cooling system capacity (incl. heating) in l (<i>US gal</i>)	19.6 (5.2)
Dimensions / body	
Body type / number of doors	Unitary steel/aluminum composite construction / 5
Number of seats	5
Drag coefficient Cd / frontal area A in m ² (<i>sq ft</i>)	0.28 (with standard exterior mirrors); 0.27 (with virtual exterior mirrors) / 2.65 (28.5)
Standard dimensions (length / width excluding mirrors / height with air springs) in mm (<i>ft</i>)	4901 (16.1) / 1935 (6.3) / 1629 (5.34) (with roof-mounted aerial), 1616 (5.30) (without roof-mounted aerial)
Width including mirrors in mm (<i>ft</i>)	2192 (7.2)
Wheelbase // track width front / rear in mm (<i>ft</i>)	2928 (9.6) // 1655 (5.43) / 1652 (5.42)
Overhang angle front / rear in degrees	15.3 / 21.5
Ramp angle in degrees	13.8
Ground clearance in mm (<i>ft</i>)	172 (0.6)
Fording depth in mm (<i>ft</i>)	300 (1.0)
Gradeability in %	50
Gradeability in degrees (gradient angle)	27
Height of loading edge in mm (<i>ft</i>)	800 (2.6)
Luggage capacity behind 2nd seat bench, open / closed in l (<i>cu ft</i>)	660 (23.3) / not available
Largest luggage compartment capacity - behind the 1st seat row in l (<i>cu ft</i>)	1725 (60.9)

* Figures depending on the chosen equipment level